

3660205000

Series 65 LED

65 SR 115-230 BLACK

Elnumber:

EAN-nr: 4036538484537

Stock code: A



The Series 65 LED Navigation lights are applicable for all vessels ≥ 20 m in length. Lights marked with anchor may also be used on inland waterways without limitation of ship's length. The LED Navigation lights fulfil all requirements of International Regulations for Preventing Collisions at Sea 1972 (COLREG) are published by the International Maritime Organization (IMO) and local rules.



Technical data	
Maximum ambient temperature (°C)	55
Minimum ambient temperature (°C)	-25
IP classification	66/67
Dimensions	
Width (mm)	176
Net weight (kg)	2,6
Height (mm)	206
Length (mm)	234
Gross weight (kg)	3
Body	
Colour of body	Black
Body material	Polycarbonate
Optic	
Optic	Clear
Material of diffuser	Polycarbonate
Angle of visibility (°)	360 (All-round)
Visibility (nm)	3

Electrical data	
Maximum frequency +5% (Hz)	60
Maximum voltage +10% (V)	230
Minimum frequency -5% (Hz)	50
Minimum Voltage -10% (V)	115
Total consumption (W)	4
Power factor	0,5
Light data	
Number of lamps	1
Number of lamps 2	1
Lamp power (W)	4
Lamp power 2 (W)	4
Light source 2	LED Red
Light source	LED Red
Termination	
Number of cable glands	2
Type of cable gland	M25-Polyamide
Maximum cable diameter	17
Minimum cable diameter	9
Remarks	
Remarks	115 - 230V AC Main / Reserve Lid: Aluminium, seawater resistant

Series 65 LED

Accessories

1
2
3
4

Fitting to E30000000
(on both, bottom and top)

Exponential bonding
for the signal and
navigation lights
with a stress housing

E300000000

E300001000 (Basic)
E300001000 (Basic)
E300001000 (Basic)
E300001000 (Basic)

E300001000 (Basic)
E300001000 (Basic)
E300001000 (Basic)
E300001000 (Basic)

134
200
40

173
100
11
18
182
145
156
170
234