



Fuse-link, low voltage, 30 A, AC 440 V, Joint service size 2, 17 x 71 mm, BS



Catalog No. 059-0125

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	30
Rated voltage			AC 440 V
Construction size			Joint service size 2
Size			17 x 71 mm
Breaking Capacity		kA	33
usable for size/applications			NATO
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88 DEF STAN 59-96

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	30
Rated voltage		V	440
Voltage type			AC
Rated switching capacity		kA	33
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/2ac01bb1-d63b-40fc-8e0b-813bc9de5990.pdf">http://www1.cooperbusmann.com/pdf/2ac01bb1-d63b-40fc-8e0b-813bc9de5990.pdf</a>
-------------------------	---