



Fuse-link, low voltage, 3 A, AC 440 V, Joint service size 1, 12 x 35 mm, BS



Catalog No. 059-0143

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	3
Rated voltage			AC 440 V
Construction size			Joint service size 1
Size			12 x 35 mm
Breaking Capacity		kA	33
usable for size/applications			NATO
Standard/Approval			BS
Shape			cylindrical
Standards/Regulations			BS88 DEF STAN 59-96

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	3
Rated voltage		V	440
Voltage type			AC
Rated switching capacity		kA	33
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/76af0d86-579c-4ccc-afb5-33295785a098.pdf
-------------------------	---