

TL60704001

TL60 LED

TL60 4500 840 110-240 M25 AS


Elnumber:

EAN-nr: 4036538552793

Stock code: A



The innovative LED outdoor lighting fixtures are applicable for a wide range of different areas, e.g. workshops, engine rooms, stores, passage ways etc. They are designed to meet maritime requirements and to save energie and maintainance cost due to extream long lifetime.



Technical data	
Maximum ambient temperature (°C)	55
IK Classification	10
Minimum ambient temperature (°C)	-35
IP classification	66/67
Dimensions	
Net weight (kg)	6,5
Height (mm)	65
Length (mm)	1280
Gross weight (kg)	7,1
Width (mm)	186
Body	
Colour of body	Silver
Body material	Aluminium seawater resistant
Material end cap	Polycarbonate
Optic	
Optic	Opal
Material of reflector	Aluminium
Colour of reflector	White
Material of diffuser	Polycarbonate
Lightdistribution Up/Down	3/97
Electrical data	
Maximum voltage +10% (V)	240
Maximum frequency +5% (Hz)	60
Minimum frequency -5% (Hz)	50
Minimum Voltage -10% (V)	110
Number of fixtures on a MCB16 type B fuse	9
Number of fixtures on a MCB16 type C fuse	13
Total consumption (W)	50
Number of fixtures on a MCB10 type B fuse	5
Number of fixtures on a MCB10 type C fuse	8
Power factor	0,92

Ballast/Driver	
Type of ballast/driver	High frequency
Number of ballast/driver	2
Light data	
Lamp code supplied light source	CRI >80, 4000K
System Lumen/Watt	90
Light source	LED White
Nominal lumen value (lm)	4500
System Lumen Out	4517
Rated system lifetime at Ta 45°C	100.000h
Termination	
Number of cable glands	2
Number of blind plugs	2
Type of cable gland	M25-Polyamide
Type of blind-plug	M25-Polyamide
Minimum cable diameter	7
Maximum cable diameter	17
Termination	3 pole double push in terminal
Ready for mounting	Flexible M8 brackets, stainless steel
Remarks	
Remarks	Cable entry: 2xM25x1.5 polyamide D9-17mm (included reduction sealing insert D7-12mm) + Blind plugs: 2xM25x1.5 polyamide With end cap and connection box Polycarbonate/white.

TL60704001

TL60 LED

Drawings

